

PRODUCT DATA SHEET

Description

CCR10 is a permanent membrane forming emulsion compound employing Pliolite® resin technology. The product is suitable for spraying onto the freshly poured concrete to give an effective and economical method of curing.

Principal uses

- CCR10 is very efficient, where light reflectance is needed to keep the temperature of the concrete to a minimum.
- To cure concrete effectively ensuring maximum strength development.
- Will act as a primer for paint systems
- Enhances adhesion of tile adhesives, joint sealants, epoxy flooring systems and polymer modified cement systems

Advantages

- Minimal delay on coatings to applied surfaces
- Will reduce the growth of bacteria
- Will act as barrier against chloride penetration
- Dust free surface

Performance data

Curing efficiencies of CCR10 has been tested by SABS and have exceeded the requirements of ASTM C309, Type 1, Class B

Gravity; 0.83

Colour; clear liquid

Appearance; water repellent clear film

Application

CCR10 is a spray applied to the newly placed concrete, care being taken to ensure complete coverage of the surface. Various types of spraying equipment can be used i.e.

Knapsack or motorized sprayers. Brush application can be used for smaller areas.

CCR10 should be applied as soon as possible after the concrete has been surface finished, i.e. trowelled, tamped or textured as required, but generally within 30 minutes or earlier if in conditions of hot sun or strong drying winds.

The nozzle of the spray should be held some 30cm to 50cm from the surface and passed slowly back and forth to ensure thorough coverage.

Packaging

CCR10 is available in 210ℓ and 25ℓ drums

Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

Shelf Life & Storage

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Note

Roll drum before use

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to Epoxerite quality control. We cannot be held responsible or liable, directly or in indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.